

**KONSTRUKT FAIRING COAT MORTAR**  
Cementitious fairing coat for pre-cast and off-form concrete

Product Code:  
MORTARFC20

Issue Date: 21/08/2015

This product is classified as hazardous according to criteria of NOHSC

**Section 1 – Identification of the Material and Supplier**

**PRODUCT (MATERIAL) NAME:** FAIRING COAT MORTAR  
**OTHER NAMES:**  
**RECOMMENDED USES:** Cementitious repair mortar where a thin layer is required  
**SUPPLIER NAME/ADDRESS:** ITLS-TWA Australia Pty Ltd – 250 Princes Hwy Dandenong Vic 3175  
**TELEPHONE NUMBER:** (03) 9791 8211 **FACSIMILE NUMBER:** (03) 9791 8644  
**EMERGENCY PHONE NUMBER:** (03) 9791 8211 **HOURS:** 0800-1700 Mon-Fri

**Section 2 – Hazards Identification**

**HAZARD CLASSIFICATION:** Classified as a HAZARDOUS SUBSTANCE according to criteria of NOHSC.  
Classified as NON-DANGEROUS GOODS according to criteria of Australia Dangerous Goods Code

**RISK PHRASES:**  
**R37/38** Irritating to respiratory system and skin.  
**R48/20** Danger of serious damage to health by prolonged exposure through inhalation  
**R41** Risk of serious damage to eyes.

**SAFETY PHRASES:**  
**S22** Do not breath dust.  
Avoid contact with eyes.  
In case of contact with eyes, rinse immediately with plenty of water and contact a doctor or Poisons Information Centre 13 11 26 (Australia-wide).  
**S28** After contact with skin, wash immediately with water (and soap if available).  
**S36/37/39** Wear suitable protective clothing, gloves and eye/face protection. S38: If insufficient ventilation, wear suitable respiratory equipment.

**Section 3 – Composition/Information on Ingredients**

**INGREDIENTS:**

Chemical Name:	Proportion:	CAS Number:
Portland cement	30 – 60%	[65997-15-1]
Crystalline silica (quartz)	30 – 60%	[14808-60-7]

Balance of formulation consists of ingredients below cut-off rates or ingredients determined not to be hazardous.

**Section 4 – First Aid Measures**

**INHALATION:** If inhaled, remove patient to fresh air. Encourage patient to blow nose and clear breathing passages. Drink water to remove dust from throat. If breathing stops, provide artificial respiration. Seek medical attention if irritation persists.

**INGESTION:** If swallowed, DO NOT induce vomiting. Rinse mouth with plenty of water. For advice, contact the Poisons Information Centre (Phone Australia-wide 13 11 26) or a doctor.

**SKIN:** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Remove contaminated clothing and wash before reuse. Wash off skin with soap and water. Seek medical assistance if irritation persists.

**KONSTRUKT FAIRING COAT MORTAR**  
Cementitious fairing coat for pre-cast and off-form concrete

Product Code:  
MORTARFC20

Issue Date: 21/08/2015

<b>EYES:</b>	If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre, or a doctor, or for at least 15 minutes. Removal of contact lenses after injury should only be undertaken by skilled personnel.
<b>FIRST AID FACILITIES:</b>	Eye wash and normal washroom facilities.
<b>ADVICE TO DOCTOR:</b>	Treat symptomatically. POISON INFORMATION CENTRE – 13 11 26 Australia-wide.
<b>EXTINGUISHING MEDIA:</b>	Select to suit surrounding fire.
<b>HAZARDS FROM COMBUSTION PRODUCTS:</b>	Not applicable.
<b>SPECIAL PROTECTIVE PRECAUTIONS AND EQUIPMENT FOR FIRE FIGHTERS:</b>	Fire fighters to wear self-contained breathing apparatus. Avoid bodily contact with substance or run-off.
<b>HAZCHEM CODE:</b>	Not applicable.
<b>ADDITIONAL INFORMATION:</b>	Not applicable.

**Section 6 – Accidental Release Measures**

**EMERGENCY PROCEDURES:**

Prevent material from entering storm water drains, waterways, basements or workpits. Wear dust mask. Wear protective goggles to prevent eye contamination. Sweep or vacuum material up without creating dust clouds. Collect material into clean, dry containers. Label containers correctly. Ensure area is thoroughly ventilated before recommencing work.

**METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN UP:**

Refer to State Land Waste Management Authority. Empty containers must be decontaminated. Normally suitable for disposal at approved land waste site.

**Section 7 – Handling and Storage**

**PRECAUTIONS FOR SAFE HANDLING:**

Wear protective goggles/face shield and rubber gloves and barrier cream to prevent eye and skin contamination. Contact lenses pose a special hazard as they may absorb irritants. Suitable protective clothing, PVC gloves and boots should be worn. Use in a well ventilated area, preferably outdoors. General exhaust is normally adequate. If risk of overexposure exists, wear SAA approved dust respirator. Avoid generation or accumulation of dusts.

**CONDITIONS FOR SAFE STORAGE:**

Keep containers tightly sealed when not in use. Store in a cool, dry, well-ventilated place and out of direct sunlight. Keep away from strong acids.

**INCOMPATIBILITIES:** No restrictions.

**Section 8 – Exposure Controls / Personal Protection**

**NATIONAL EXPOSURE STANDARDS:**

Exposure to dust should be kept as low as practicable, and below the NES for the product as listed below:  
Crystalline silica (quartz) – 0.1 mg/m<sup>3</sup> TWA as respirable dust  
Dust (NOS- not otherwise specified) - 10mg/m<sup>3</sup> TWA as inspirable dust.

**KONSTRUKT FAIRING COAT MORTAR**  
Cementitious fairing coat for pre-cast and off-form concrete

Product Code:  
MORTARFC20

Issue Date: 21/08/2015

<b>BIOLOGICAL LIMIT VALUES:</b>	Not established for the product.
<b>ENGINEERING CONTROLS:</b>	If used in limited ventilation, ensure adequate ventilation to maintain exposure levels are kept below standards, by using a local exhaust. Keep containers closed when not in use.
<b>PERSONAL PROTECTION:</b>	Avoid unnecessary contact as good work practice. Wash contaminated clothing and protective equipment before storing and reuse. Wash hands before eating, smoking or using the toilet.
<b>RESPIRATORY PROTECTION:</b>	The use of a respirator or other device is recommended where dust is being generated. For assistance in selecting suitable equipment consult AS/NZ1715.
<b>EYE PROTECTION:</b>	Eye protective measures are normally necessary, and are suggested when using this product. Consult AS1336 and AS/NZ1337.
<b>PROTECTIVE GLOVES:</b>	Rubber, PVC or other protective gloves are necessary, and desirable, especially if this product is being used frequently or for lengthy periods. Consult AS2 161 for guidance.
<b>CLOTHING:</b>	Clean overalls should be worn, preferably with an apron. Consult AS2919 for clothing guidance.
<b>SAFETY FOOTWEAR:</b>	Wearing safety boots is advisory. Consult AS/NZ2210 for advice on Occupational Protective Footwear.

**Section 9 – Physical and Chemical Properties**

**APPEARANCE (COLOUR, PHYSICAL FORM, SHAPE):**

Fine grey powder

<b>ODOUR:</b>	None
<b>VAPOUR PRESSURE:</b>	Negligible
<b>MELTING POINT:</b>	Not available
<b>BOILING POINT:</b>	Not applicable
<b>SOLUBILITY:</b>	Partly miscible in water
<b>SPECIFIC GRAVITY:</b>	1.5
<b>FLASH POINT:</b>	Non-combustible
<b>UPPER FLAMMABLE LIMIT:</b>	Not applicable
<b>LOWER FLAMMABLE LIMIT:</b>	Not applicable
<b>VOLATILE ORGANIC COMPOUNDS (VOC) CONTENT:</b>	Not stated.

**Section 10 – Stability and Reactivity**

<b>CHEMICAL STABILITY:</b>	Stable.
<b>CONDITIONS TO AVOID:</b>	Keep away from strong acids.
<b>INCOMPATIBLE MATERIALS:</b>	No restrictions
<b>HAZARDOUS DECOMPOSITION PRODUCTS:</b>	Product is not combustible, however containers may burn.
<b>HAZARDOUS REACTIONS:</b>	None

**KONSTRUKT FAIRING COAT MORTAR**  
Cementitious fairing coat for pre-cast and off-form concrete

Product Code:  
MORTARFC20

Issue Date: 21/08/2015

**Section 11 – Toxicological Information**

**TOXICOLOGY INFORMATION:** No toxicity data is available for this specific product, however toxicity data found for constituents are stated below:

This product contains a proportion of respirable free crystalline silica in the quartz component. Crystalline silica is classified as a Class 1 Human Carcinogen according to IARC (International Agency for Research on Cancer), however research on this is inconclusive and the ASCC/NOHSC has yet to classify crystalline silica as a human carcinogen. Current research indicates no excess risk of lung cancer or other cancers from using these products. Repeated exposure to respirable crystalline silica dust may lead to silicosis, or other serious delayed lung injury. The onset of silicosis is usually slow and lung damage may occur even when no symptoms or signs of ill-health have occurred. Silicosis can develop to a more serious degree even after exposure has ceased, and may also lead to other diseases including heart disease and scleroderma. Inhalation of dust, including crystalline silica dust, is considered by medical authorities to increase the risk of lung disease due to tobacco smoking.

**HEALTH EFFECTS FROM THE LIKELY ROUTES OF EXPOSURE:**

- INHALATION:** The dust is highly irritating to the upper respiratory tract and lungs, and may cause coughing and sneezing. Persons with pre-existing respiratory conditions may incur further disability if excessive concentrations of material are inhaled. Overexposure may cause coughing, wheezing and irritation of nasal passages.
- INGESTION:** Highly irritating and mildly corrosive if swallowed. May result in nausea, abdominal irritation, pain and vomiting. Ingestion is not expected to occur in normal industrial use.
- EYES:** The dust is highly irritating and abrasive to the eyes and is capable of causing pain and severe conjunctivitis. Corneal injury may develop, with possible permanent impairment of vision if not promptly and properly treated.

**Section 12 – Ecological Information**

- ECOTOXICITY:** Not available
- PERSISTENCE AND DEGRADABILITY:** Not available
- MOBILITY:** Not available
- ENVIRONMENTAL PROTECTION:** Not expected to create environmental hazards unless dumped in massive quantity.

**DISPOSAL METHODS AND CONTAINERS:**

Refer to State Land Waste Management Authority. Empty containers must be decontaminated. Normally suitable for disposal at approved land waste site.

**Section 13 – Transport Information**

- UN NUMBER:** None assigned
- UN PROPER SHIPPING NAME:** None assigned
- CLASS AND SUBSIDIARY RISK:** None assigned
- PACKING GROUP:** None assigned
- HAZCHEM CODE:** None assigned
- SPECIAL PRECAUTIONS PER USER:**

Keep containers tightly sealed when not in use. Store in a cool, dry, well-ventilated place and out of direct sunlight. Keep away from strong acids. No regulatory requirements apply to the transport of this product.

**KONSTRUKT FAIRING COAT MORTAR**  
Cementitious fairing coat for pre-cast and off-form concrete

Product Code:  
MORTARFC20

Issue Date: 21/08/2015

**Section 14 – Regulatory Information**

**POISON SCHEDULE:** Not scheduled  
**OHS:** Unregulated  
**ENVIRONMENTAL:** Unregulated  
**ADDITIONAL NATIONAL AND/OR INTERNATIONAL REGULATORY INFORMATION:**  
Unregulated

**Section 15 – Other Information**

**DATE OF PREPARATION OR LAST REVISION OF MSDS:**

8 June 2011

**REASON FOR REVISION:** Revise company details

**CONTACT POINT:** ITLS-TWA Australia Pty Ltd  
(03) 9791 8211

**LITERATURE REFERENCES / SOURCES OF DATA:**

Material Safety Data Sheets from Suppliers  
List of Designated Substances – Worksafe Australia (on-line) Australian Dangerous Goods Code 6th Edition  
Standard for the Uniform Scheduling of Drugs and Poisons No 19  
The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of seller's knowledge, however seller makes no warranty whatsoever, expressed, implied, or of merchantability regarding the accuracy of such data or the results to be obtained from the use thereof. Seller assumes no responsibility for injury to buyer or third persons or for any damage to property. Buyer assumes all risks.

The information and any recommendations relating to the application and end-use of all Konstrukt products are provided in good faith based on Synergy knowledge and experience of the products. In applications, the differences in materials, and variances of substrates and actual site conditions can vary such that no warranty in respect of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be taken as inferred either from this information, or from any written recommendations, or from any other advice offered by Synergy. The proprietary rights of third parties must be observed. All orders are accepted subject to our sale terms and conditions. All users should always refer to the most recent and up to date issue of the Technical Data Sheet for the product concerned, which is available on request. It

is recommended that products should always be properly stored, handled and applied under tested and recommended conditions.

PLEASE CONSULT OUR TECHNICAL DEPARTMENT FOR FURTHER INFORMATION.