


PRODUCT CODE: KONS-DMP2V

FEATURES & BENEFITS

- Certified to AS/NZS 1716:2012 Respiratory Protective Devices.
- P2 disposable respirator for protection against mechanically & thermally generated particles.
- Lightweight cupped design for comfortable extended wear.
- Dual latex free elastic straps for ease of donning & doffing.
- ProValve exhalation valve for decreased breathing resistance & heat stress.
- Easily worn with glasses & goggles.
- Resealable bag for hygienic storage.

CARE INSTRUCTIONS

Shelf life of the unopened product is 3 years from date of manufacture when stored within temperature range of -20°C to +25°C & less than 80% relative humidity.

Manufactured date printed onto filters, maximum life span is 6 months once filter is removed from original packaging, however life span is determined by the wearers ability to taste, smell or notice increase in breathing resistance.

Ensure mask is correctly fitted prior to each use & conduct annual fit testing in accordance with AS/NZS 1715:2009.

AVAILABLE IN

PRODUCT CODE	QTY	CARTON
KONS_DMP2V	12 pieces	20 boxes

PRODUCT DETAILS

Straps: Latex-Free Rubber Band
Filter Media: Polypropylene Melt-Down
Weight: 14.2g ± 1

WARNINGS & USE LIMITATIONS

1. Facial hair has the potential to compromise the required protective seal of the respirator.
2. Ensure adequate oxygen levels are present.
3. Ensure the contamination is known & the respirator is suitable for the application.
4. Replace when taste, smell or the breathing resistance is high.
5. Store in a clean resealable storage device.

STANDARDS

Certified to:

AS/NZS 1716:2012 Respiratory Protective Devices
 Certified by Benchmark

To be used in conjunction with:

AS/NZS 1715:2009 -

Selection, use & maintenance of respiratory protective equipment



AS/NZS1716:2012
 ID No: BMP547903

Classification	Efficiency	Examples of Contaminants / Uses
P1	80% (Particles to 1µm micron = 0.001mm size)	Dust
P2	94% (Particles to 0.3µm micron = 0.0003mm size)	Toxic dusts including asbestos, welding fumes
P3	99.95% (Particles to 0.3µm micron = less than 0.0003mm size)	Toxic dusts including asbestos, welding fumes, full face & powered air performance at P3 only